

All OCX2 series products are made of the best stainless steel quality and are equipped with the new Steelock system for opening-closing and ventilation in periods of non-use. These are reliable high-performance products, designed to face any journey or situation in conditions of absolute comfort, allowing you to eat and drink just like being

at home. Even better. The DRW series offers three all in one products: you can set the desired temperature (fridge or freezer) anytime, using a digital thermostat with the latest generation touch screen. Wide drawers, with cushioned sliding, in totally no-frost mode. The DW OCX2 series allows precise temperature regulation by means of a digital thermostat, offering drawer solutions for any refrigeration need: fridge only - fridge-freezer and with internal icemaker. The Steel

OCX2 series, equipped with a mechanical thermostat, offers the same performance and versatility as the Chromelock series, in stainless steel finishing. The stainless steel range is completed by the two new CFR, all-in-one refrigerator-freezers and the Icemaker series - both in the OCX2 version with 230Vac power supply and ice production equal to 8kg./24h and in the 12Vdc power supply version with production of ice equal to 4kg./24h.

DRW-ALL IN ONE



	DRW 360A	DRW 180A	DRW 70A
Total volume Capacità totale (lt.)	157+150	150	80
Freezer compartment Vano freezer (lt.)			
Fridge+freezer Frigo+freezer	ALL-IN ONE	ALL-IN ONE	ALL-IN ONE
Fridge Frigo			
Weight Peso (kg.)	100	55	38
Internal icemaker Icemaker interno			
Dimensions Dimensioni (mm.)	A = 682 B = 585 H = 1740	666 590 874	666 590 467
Drawer opening Apertura a cassetto	•	•	•
Front opening Apertura frontale	•		
Stainless steel finishing Finitura in acciaio inox	•	•	•
Compressor Compressore	•	•	•
Holding plate version Evaporatore a accumulo			
Built-in cooling unit Unità refrigerante interna	•	•	
Remote cooling unit Unità refrigerante esterna			•
Standard power supply Alimentazione standard (Vdc)	12/24	12/24	12/24
Optional power supply Alimentazione optional (Vac)	12/24 100-240	12/24 100-240	12/24 100-240
Nominal consumption Consumo nominale (W)	*** + 96	96	96
Digital thermostat Termostato digitale	•	•	•
Mechanical thermostat Termostato meccanico			
Internal Led light Luce interna a Led	•	•	•
Reversible door Porta reversibile	•		
Vent position Posizione di ventilazione	•	•	•
Page nr. - Pagina n.	16	17	17

* RFX version weight.
Peso in versione RFX.

** RFX version nominal consumption.
Consumo nominale in versione RFX.

For further versions (BTX, DTX, IM etc.) please see product page.
Per le altre versioni (DTX, BTX, IM ecc), consultare la pagina prodotto.