

Intuitive User Interface and White Backlit LCD and Keypad

Incorporating Icom's common Marine Family User Interface designed for simple, intuitive operation. A rotary selector and directional keypad provide quick and easy access to the intended functions. The high contrast white backlit LCD and laser-cut keypad match well with modern boat designs.

Active Noise Cancelling

The built-in active noise cancelling provides superb performance. It reduces background noise up to 90% in the received signal and 30% in the transmits signal.

10 W Loud Audio, Public Address and Foghorn

The IC-M423GE has a built-in 10 W amplifier that increases the audio output to an external PA speaker. The public address function allows you to make an announcement from the microphone like a loud speaker, the foghorn can also be emitted from the external PA speaker.

Built-in Class D DSC

The built-in DSC watch function monitors Ch. 70 (DSC channel) activity, even while you are receiving another channel. DSC functions include: distress, individual, group, all ships, urgency, safety, position request/report, polling request and DSC test calls.

Built-in GPS Receiver

The built-in GPS receiver shows your current position, date/time and can be used for DSC calls.



Supplied GPS antenna

Optional White Backlit COMMANDMIC™ HM-195GB/GW

The optional white backlit COMMANDMIC makes it convenient for using the IC-M423GE from a separate cabin or tower. All functions of the IC-M423GE can be controlled from the COMMANDMIC and can be used as an intercom with the IC-M423GE.

AIS Target Call with MA-510TR

When connected to the optional MA-510TR Class B AIS transponder, the AIS target call function allows you to make an individual DSC call without having to manually input an MMSI number.

And More

- Remote control speaker-microphone, HM-205B/SW
- NMEA 0183 connectivity
- MarineCommander™ compatible
- AquaQuake™ draining function
- IPX7 waterproof protection
- Dual/tri-watch function
- Priority and normal scan
- Black and super white versions available.
- Supports 4-digit channels

SPECIFICATIONS

GENERAL		
Frequency range	TX RX CH70	156.000–161.450 MHz 156.000–163.425 MHz 156.525 MHz
Usable channels		INT, USA* channels * Available depending on version
Type of emission		16K0G3E (FM), 16K0G2B (DSC)
Power supply requirement		3.8 V DC nominal (10.8–15.6 V DC)
Current drain (at 12.0 V DC)	Tx 25 W output Rx AF max. External SP Internal SP	5.5 A 5.0 A (RX SP ON) 1.5 A
Operating temperature range		–20°C to +60°C
Antenna impedance		50 Ω (SO-239)
Dimensions (W×H×D) (projections not included)		180×82×119.9 mm
Weight (approx.)		1.2 kg
NMEA in/out formats		RMC, GGA, GNS, GLL, DSC, DSE
TRANSMITTER		
Output power (at 12.0 V DC)		25 W, 1 W
Max. frequency deviation		±5.0 kHz
Frequency stability		Less than ±1.5 kHz
Spurious emissions		Less than 0.25 µW
RECEIVER		
Sensitivity (20 dB SINAD)		–5 dBµ emf typ.
Squelch sensitivity		less than –2 dBµ emf
Adjacent channel selectivity		More than 70 dB
Spurious response		More than 70 dB
Intermodulation		More than 68 dB
Audio output power (at 10% distortion, 4 Ω load)		More than 10 W (Ext. speaker)
GPS RECEIVER		
Receiving frequency		1575.42 MHz
Receiving channels		66 channels
Satellite differential type		WAAS, EGNOS, MSAS, GAGAN

Measurements made in accordance with EN 301 025-2, -3. All stated specifications are subject to change without notice or obligation.

Applicable IP Rating

Ingress Protection Standard	
Water	IPX7 (Waterproof protection)

Supplied accessories:
• Hand microphone, HM-205B/SW • DC power cable
• Mounting bracket kit • GPS antenna

OPTIONS

<p>COMMANDMIC™</p> <p>HM-195GB (Black) HM-195GW (Super white)</p> <p>Supplied accessories</p> <ul style="list-style-type: none"> • 6.1 m (20 ft) of cable • Microphone hanger • Mounting base for connector 	<p>EXTENSION CABLE for COMMANDMIC, HM-195GB/GW</p> <p>OPC-1541 6.1 m (20 ft) extension cable. Up to two cables available.</p>	<p>SPEAKER-MICROPHONE</p> <p>HM-205B/SW Same as supplied.</p>	<p>FLUSH MOUNT KIT</p> <p>MB-132</p>	<p>CLASS B AIS TRANSPONDER</p> <p>MA-510TR</p>
--	--	--	---	---

Amber backlit COMMANDMIC, HM-195B/HM-195SW are also available.