

All OCX2 series products are made of the best stainless steel quality and are equipped with the new Steelock system for opening-closing and ventilation in periods of non-use. These are reliable high-performance products, designed to face any journey or situation in conditions of absolute comfort, allowing you to eat and drink just like being

at home. Even better. The DRW series offers three all in one products: you can set the desired temperature (fridge or freezer) anytime, using a digital thermostat with the latest generation touch screen. Wide drawers, with cushioned sliding, in totally no-frost mode. The DW OCX2 series allows precise temperature regulation by means of a digital thermostat, offering drawer solutions for any refrigeration need: fridge only - fridge-freezer and with internal icemaker. The Steel


OCX2 series, equipped with a mechanical thermostat, offers the same performance and versatility as the Chromelock series, in stainless steel finishing. The stainless steel range is completed by the two new CFR, all-in-one refrigerator-freezers and the Icemaker series - both in the OCX2 version with 230Vac power supply and ice production equal to 8kg./24h and in the 12Vdc power supply version with production of ice equal to 4kg./24h.

ICEMAKER

230V

12V



	IM XT / XR OCX2 ****	IM CL OCX2 ****	IM XT ****	IM CL ****
Total volume Capacità totale (lt.)	24	24	24	24
Freezer compartment Vano freezer (lt.)	ICE PROD.	ICE PROD.	ICE PROD.	ICE PROD.
Fridge+freezer Frigo+freezer	8,0 kg./24h	8,0 kg./24h	4,0 kg./24h	4,0 kg./24h
Fridge Frigo				
Weight Peso (kg.)	25 / 27	23	28	26
Internal icemaker Icemaker interno				
Dimensions Dimensioni (mm.)	 A = 416 B = 435/555 H = 546	416 435 702	387 516 485	387 370 641
Drawer opening Apertura a cassetto				
Front opening Apertura frontale	•	•	•	•
Stainless steel finishing Finitura in acciaio inox	•	•	•	•
Compressor Compressore	•	•	•	•
Holding plate version Evaporatore a accumulo				
Built-in cooling unit Unità refrigerante interna	• (XT)	•	•	•
Remote cooling unit Unità refrigerante esterna	• (XR)			
Standard power supply Alimentazione standard (Vdc)			12	12
Optional power supply Alimentazione optional (Vac)	230	230		
Nominal consumption Consumo nominale (W)	180	180	180	180
Digital thermostat Termostato digitale	•	•		
Mechanical thermostat Termostato meccanico			•	•
Internal Led light Luce interna a Led				
Reversible door Porta reversibile	•	•	•	•
Vent position Posizione di ventilazione	•	•	•	•
Page nr. - Pagina n.	40	41	42	43

* RFX version weight.
Peso in versione RFX.

** RFX version nominal consumption.
Consumo nominale in versione RFX.

For further versions (BTX, DTX, IM etc.) please see product page.
Per le altre versioni (DTX, BTX, IM ecc), consultare la pagina prodotto.